



Change for Life

Submittal Data :Cassette Units		GKH<24>BA-D3DNA1A/I	
Job Name :		Date :	
Engineer :		Submitted to :	
Location :		Submitted by :	
Tag # :		Schedule / Drawing # :	
For :	<input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction		

- GENERAL FEATURES**
- Quiet Operation -Multi-Speed Fan
 - 4-way Discharge Air
 - Internal Condensate Drain Pump
 - Swing Louver
 - Both Wireless & Wired Remote Controllers
 - Power Failure Recovery
 - Sentry Condensate Overflow Protection
 - Flare connection
 - Decorative Grille



Cooling		Air Flow	
Cooling Capacity	22,800 Btu/h	Air Flow Volume	694/559/500 CFM
Cooling Speed	620/570/520 r/min	Sound Pressure Level	/39/ /37/ /35/ dB(A)
Recommended Power Cable(Core)	4	Sound Power Level	/49/ /47/ /45/ dB(A)
Cross-sectional Area of Power Cable Conductor	AWG18 <0.82>		
		Electrical	
		Power supply	208V-1Ph -60Hz
Heating Capacity	27,400 Btu/h	Fuse Current	3 A
		Fan Motor Power Output	50 W
		Number of fans	1 N
		Fan Type	Centrifugal
Set Temperature Range ° F	61 ~ 86		

Physical & Piping			
Base Unit Dimension (WxDxH)	840x840x240 mm	Liquid Line connection	3/8 in
Net Weight	28 kg	Gas connection	5/8 in
Panel Net Weight	6.5 kg	Panel Dimension(LxWxH)	950x950x60 mm



1-833-666-GREE
www.greehvac.ca

Manufacturer has right to change the data without notice, please refer to the name plate of the unit.